



Main

| | |
|---------------------------|-----------------------|
| Range | Masterpact |
| Product or component type | Switch disconnecter |
| Device application | Distribution |
| Switch-disconnector name | Masterpact MTZ2 40 HA |
| Poles description | 3P |
| Network type | AC |
| Network frequency | 50/60 Hz |

Complementary

| | |
|---|--|
| Control type | Push-button |
| Mounting mode | Drawout |
| Mounting support | Chassis |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 |
| [Ie] rated operational current | 4000 A AC 50/60 Hz 690 V |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to EN/IEC 60947-3 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to EN/IEC 60947-3 |
| [Icw] rated short-time withstand current | 66 kA during 1 s conforming to EN/IEC 60947-3 55 kA during 3 s conforming to EN/IEC 60947-3 |
| [Icm] rated short-circuit making capacity | 145 kA peak 220...690 V AC at 50/60 Hz |
| Utilisation category | AC-23A AC-3 |
| Breaking capacity | 66 kA Icu at 220...690 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| [Ics] rated service breaking capacity | 66 kA at 220...690 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Performance level | HA |
| Suitability for isolation | Yes conforming to EN/IEC 60947-3 |
| Contact position indicator | Yes |
| Visible break | No |
| Mechanical durability | 20000 cycles with periodic preventive maintenance conforming to EN/IEC 60947-3 |
| Electrical durability | AC-23A: 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 |
| Connection pitch | 150 mm |
| Height | 439 mm |
| Width | 441 mm |
| Depth | 403 mm |

Environment

| | |
|---------------------------------------|----------------------------------|
| Net weight | 90 kg |
| Standards | EN/IEC 60947-3 |
| Product certifications | IECEE CB Scheme |
| IP degree of protection | IP30 |
| Pollution degree | 3 conforming to EN/IEC 60947-4-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|