



### Main

Range of product	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICMB
Device application	Electrical circuit control
Contacts type and composition	2 C/O
[Ue] rated operational voltage	415 V AC 50/60 Hz
Standards	VDE 0660 part 107 IEC 60947-3 EN 60947-3 UL

### Complementary

[Ie] rated operational current	10 A
Maximum operating voltage	440 V
Control type	Rotary handle 3 positions
Marking	1 - 0 - 2
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Net weight	58 g
Colour	White
Mechanical durability	1000000 cycles
Electrical durability	AC-21A: 200000 cycles
Connections - terminals	Jumper terminals 1.5 mm <sup>2</sup>
Wire stripping length	9 mm for downside connection
Tightening torque	1 N.m downside

### Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	74 g
Package 1 Height	4.3 cm
Package 1 width	7.6 cm
Package 1 Length	8.4 cm
Unit Type of Package 2	S03
Number of Units in Package 2	80

Package 2 Weight	6.407 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------