

# Product data sheet

## Characteristics

# 9422CSF10

Disconnect mechanism, circuit breaker, cable operated, 150/250A, 3 pole, PowerPact H and J breaker, 120 inch cable



### Main

Range	9422C
Product	Single Cable Operating Mechanism

### Complementary

Circuit Breaker Type	MG-NSF 2 MG-NSF 3 PowerPact H or J 2 PowerPact H or J 3
Included	Ordered separately
Number of Cables	1
Cable Length	120 in

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.862 kg
Package 1 Height	17.78 cm
Package 1 width	31.75 cm
Package 1 Length	34.29 cm

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.