Product data sheet Characteristics

A9MEM3300 iEM3300 energy meter - 125 A





Main

Range	Acti 9
Range of product	Acti 9 iEM3000
Device short name	IEM3300
Product or component type	Energy meter

Complementary

Poles description	1P + N	
	3P + N	
	3P	
Type of measurement	Active energy	
Device application	Partial meter	
	Sub billing	
Accuracy class	Class 1 active energy conforming to IEC 62053-21	
	Class 1 active energy conforming to IEC 61557-12	
	Class B active energy conforming to EN 50470-3	
Input type	Direct input	
[In] rated current	125 A	
Rated voltage	100277 V	
	173480 V	
Network frequency	50 Hz	
	60 Hz	
Technology type	Electronic	
Display type	LCD display	
Sampling rate	32 samples/cycle	
Measurement current	0125 A	
Maximum value measured	99999999.9 kWh	
Communication port protocol	-	
Communication port support	-	
Local signalling	Green indicator light: power ON	
	Yellow flashing LED: accuracy checking	
Number of inputs	0	
Number of outputs	0	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Connections - terminals	Screw terminals 50 mm² cable(s)	
Overvoltage category	III	

IEC 61036	
IEC 61010	
IEC 62053-21	
IEC 61557-12	
UL 61010-1	
IEC 62053-23	
CE conforming to IEC 61010 (safety)	
CE conforming to EN 61557-12 (power monitor)	
CE conforming to IEC 61326-1 (EMC)	
CULus conforming to UL 61010 (safety)	
CULus conforming to ANSI C12.20 (sub-meter)	
EAC (sub-meter)	
RCM conforming to NMI M 6-1 (sub-meter)	
UL	
	IEC 61010 IEC 62053-21 IEC 61557-12 UL 61010-1 IEC 62053-23 CE conforming to IEC 61010 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to IEC 61326-1 (EMC) CULus conforming to UL 61010 (safety) CULus conforming to ANSI C12.20 (sub-meter) EAC (sub-meter) RCM conforming to NMI M 6-1 (sub-meter)

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529	
Pollution degree	2	
Relative humidity	595 % at 50 °C	
Ambient air temperature for operation	-2560 °C - IEC	
Ambient air temperature for storage	-4085 °C	
Operating altitude	< 2000 m	
Colour	White	
9 mm pitches	14	
Width	126 mm	
Height	103.2 mm	
Depth	69.3 mm	

Packing Units

Package 1 Weight	0.687 kg	
Package 1 Height	8.500 cm	
Package 1 width	11.200 cm	
Package 1 Length	13.100 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Environmental Disclosure	[™] Product Environmental Profile	_