
LV833034SP

XF or MX voltage release, diagnostics and communicating, Masterpact MTZ1/2/3, 48 VAC 50/60 Hz, 48/60 VDC, spare part





Main	
Range	Masterpact
Product or component type	Voltage release
Device application	Control
Range compatibility	Masterpact MTZ1 circuit-breaker Masterpact MTZ2 circuit-breaker Masterpact MTZ3 circuit-breaker
Voltage release type	Closing coil Opening coil

Complementary

Control time	Communicating	
Control type	Communicating	
Signalling function	Ready to close or open	
	Electrical push-button activated	
	Error	
	Coil powered	
[Un] voltage power supply	48/60 V AC 50/60 Hz	
	48/60 V DC	
Threshold tripping voltage	0.71.1 Un on opening	
	0.851.1 Un on closing	
Holding power consumption	4.5 W	
Circuit breaker mounting mode	Fixed/drawout	
Maximum response time	60 ms on opening for Masterpact MTZ1	
	60 ms on opening for Masterpact MTZ2	
	60 ms on opening for Masterpact MTZ3	
	65 ms on closing for Masterpact MTZ1	
	80 ms on closing for Masterpact MTZ2	
	90 ms on closing for Masterpact MTZ3	
Provided equipment	1 instruction sheet	
Offer type	Spare part	

Packing Units

Package 1 Weight	0.218 kg	
Package 1 Height	0.340 dm	
Package 1 width	0.600 dm	
Package 1 Length	0.850 dm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information