



Main

| | |
|------------------------------|-----------------------------|
| Device short name | MN |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | PowerPact B ComPact NSXm |
| Voltage release type | Undervoltage release |
| [Uc] control circuit voltage | 250 V DC |

Complementary

| | |
|-------------------------------|--|
| Threshold tripping voltage | 0.35...0.7 x Un opening 0.85 x Un closing |
| Mounting mode | Clip-on |
| Response time | < 50 ms |
| Auxiliary connection terminal | Spring |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.092 kg |
| Package 1 Height | 1.500 cm |
| Package 1 width | 5.700 cm |
| Package 1 Length | 6.300 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.