



Main

Product or component type	Communication card
Range compatibility	Altivar 71 Altivar 71Q Altivar 61Q Altivar 61
Communication port protocol	Interbus
Connector type	9-way male SUB-D connector 9-way female SUB-D connector

Complementary

Communication service	Communication monitoring I/O data Abort communication relationship Communication and drive status Identification of the card Initialize communication relationship Profile 21 Read object description Read parameter Write parameter
Supply	By drive but necessary to use an external supply if the inverter is not powered
Display type	1 LED for BA (periodic data) 1 LED for RC (bus input) 1 LED for Rd (bus output) 1 LED for TR (messaging) 1 LED for U (power supply) Graphic display terminal for control word received Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	290 g
Package 1 Height	7.2 cm
Package 1 width	17 cm
Package 1 Length	23.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
