



### Main

Product or component type	Extended I/O card
Range compatibility	Altivar 61Q Altivar Lift Altivar 71Q Altivar 71 Altivar 61
Supply	Internal supply for reference potentiometer, 10.5 V DC (10...11 V) , <0.01 A, impedance: 1...10 kOhm for overload and short-circuit protection Internal supply, 24 V DC (21...27 V) , <0.2 A for overload and short-circuit protection
Analogue input number	2
Analogue input type	AI3-/AI3+ differential current programmable: 0...20 mA, impedance: 250 Ohm, sampling time: 4...6 ms, resolution: 11 bits + sign AI4 software-configurable current: 0...20 mA, impedance: 250 Ohm, sampling time: 4...6 ms, resolution: 11 bits AI4 software-configurable voltage: 0...10 V DC, 24 V max, impedance: 30000 Ohm, sampling time: 4...6 ms, resolution: 11 bits
Analogue output number	2
Analogue output type	AO2 software-configurable current: 0...20 mA, impedance: 500 Ohm, sampling time: 4...6 ms, resolution: 10 bits AO2 software-configurable voltage: +/- 10 V DC, impedance: 470 Ohm, sampling time: 4...6 ms, resolution: 10 bits AO3 software-configurable current: 0...20 mA, impedance: 500 Ohm, sampling time: 4...6 ms, resolution: 10 bits AO3 software-configurable voltage: +/- 10 V DC, impedance: 470 Ohm, sampling time: 4...6 ms, resolution: 10 bits
Discrete output number	5
Discrete output type	(LO3, LO4) assignable logic, sampling time: 4...6 ms, compatible with level 1 PLC (R4A, R4B, R4C) configurable relay logic
Discrete output logic	(LO3, LO4) negative (LO3, LO4) positive
Discrete input number	6
Discrete input type	(RP) frequency control, sampling time: 4...6 ms (LI11...LI14) programmable, compatible with level 1 PLC, impedance: 3.5 kOhm, sampling time: 4...6 ms
Discrete input logic	Negative (LI11...LI14), >= 16 V (state 0), <= 10 V (state 1) Positive (LI11...LI14), <= 5 V (state 0), >= 11 V (state 1) Positive (RP), < 1.2 V (state 0), >= 3.5 V (state 1)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Electrical durability	100000 cycles for configurable relay logic
Discrete output voltage	24 V DC (voltage limits: <= 30 V) assignable logic
Maximum output current	0.2 A, assignable logic
Minimum switching current	3 mA at 24 V DC for configurable relay logic
Maximum switching current	Configurable relay logic 5 A at 250 V AC on resistive load, cos phi = 1 Configurable relay logic 5 A at 30 V DC on resistive load, cos phi = 1 Configurable relay logic 1.5 A at 250 V AC on inductive load, cos phi = 0.4 and L/R = 7 ms Configurable relay logic 1.5 A at 30 V DC on inductive load, cos phi = 0.4 and L/R = 7 ms
PTC probe input	TH2+, TH2- trip resistance, impedance: 3 kOhm TH2+, TH2- reset resistance, impedance: 1.8 Ohm TH2+, TH2- short circuit protection, impedance: < 0.05 Ohm TH2+, TH2- for 6 PTC probe, impedance: <= 1.5 Ohm
Discrete input voltage	24 V DC (voltage limits: <= 30 V) for programmable
Discrete input frequency	0...30 kHz frequency control
Electrical connection	Terminal, 1.5 mm <sup>2</sup> / AWG 16, 0.25 N.m
Net weight	0.3 kg

## Packing Units

Package 1 Weight	0.388 kg
Package 1 Height	0.700 dm
Package 1 width	1.700 dm
Package 1 Length	2.300 dm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------