



Main

Range of product	BC Imprego
Product or component type	Dry type transformer
Network type	AC
Type of installation	Indoor

Complementary

Type of cooling	AN (air natural)
Rated power	6.3 kVA
Network frequency	50/60 Hz
Thermal class	Class H
Phase description	1 phase
Primary voltage	400 V 231 V
Isolation level	1.1 kV primary 1.1 kV secondary
[Ui] rated insulation voltage	Primary circuit: 1.1 kV AC Secondary circuit: 1.1 kV AC
Secondary voltage	115 V 220 V
Vector group	Li00
Tapping link range	+/- 5 %
Total number of steps	2
Temperature rise	125 K (winding)
Impedance voltage	4.9 %
No-load losses	70 W
Load losses	270 W
Operating altitude	< 1000 m
Winding material	Copper
Temperature class	H
Insulation material	Impregnated (LV)
Mounting mode	Fixed
IP degree of protection	IP21
IK degree of protection	IK07
Colour code	RAL 9003
Net weight	65 kg
Height	710 mm
Width	540 mm
Length	480 mm
Sound power level	65 dB at 1 m


Environment

Ambient air temperature for operation	-25...40 °C for C4
Ambient air temperature for storage	-25...50 °C C2
Environmental certification	0...93 % (E2)
Fire certificate	F1
Atmospheric-corrosivity category	C3
Standards	EN/IEC 61558-2-4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	75 kg
Package 1 Height	47 cm
Package 1 width	54 cm
Package 1 Length	71 cm

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------