



### Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MD
Actuator model	MD5B-230
Product destination	dampers
Actuator	Rotary
Control type	Automatic reset
Rated supply voltage	230 V AC
Transformer rated power in VA	3.5 VA
Power consumption in W	1.5 W
Power consumption in VA	1.5 VA AC
Hold-in power consumption in W	0.4 W
Hold-in power consumption in VA	3.5 VA AC
Control signal	2-position (on/off)
Power loss return	Non-spring return
Stroke auto calibration	False
Electrical insulation class	Class II
Tightening torque	44 lb.in 5 N.m
Position indicator	Visual indicator with position ring
Lead length	1 m
Actuator rotation	95 °
Rotational range adjustment	95° maximum (limited by an adjustable end stop)
Stroke running time	150 s
IP degree of protection	IP43
Ambient air temperature for operation	-30...50 °C
Relative humidity	0...95 % RH, non-condensing
Ambient air temperature for storage	-40...80 °C
Targeted region	Europe Asia Pacific. Australia.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	11.2 cm
Package 1 Length	18.7 cm
Package 1 Weight	480.0 g

## Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>