

Product data sheet

Characteristics

ABWRM104L01

Empty enclosure, Pragma Multi, (W) 300mm x (H) 650mm x (D) 160mm, 1 field of 4 rows, with ventilated door



Main

Range	Pragma
Product name	Pragma Multi
Product or component type	Empty enclosure
Device application	Distribution
Enclosure type	Modular enclosure

Complementary

Enclosure material	Sheet steel plastic coated, RAL 9016
Enclosure mounting	Surface
Number of fields	1
Number of rows	4
Device composition	Enclosure Door Ventilation louvres for door Plastic insert for door
Door type	Plain
Door opening side	Right or left
Lock type	Standard lock rotary Cylinder lock pivoting lever (to be ordered separately)
Cable entry	With knock-outs
[In] rated current	250 A
Rated voltage	400 V AC 50 Hz
Electrical insulation class	Class II
Width	300 mm
Height	650 mm
Depth	160 mm

Environment

IP degree of protection	IP30
IK degree of protection	IK10
Standards	EN 62208 DIN VDE 0603 part 1
Quality labels	VDE CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.44 cm
Package 1 Width	30 cm
Package 1 Length	16.96 cm
Package 1 Weight	6.38 kg

Unit Type of Package 2	P12
Number of Units in Package 2	21
Package 2 Height	108 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	76.2 kg

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------