ABWRS112

Empty enclosure, Prisma XS, floor-standing, with door, IP44, (W) 300mm x (H) 1980mm x (D) 210mm



Main Range Prisma Product name Prisma XS Product or component Enclosure type Enclosure type Empty enclosure Enclosure/cubicle Floor-standing enclosure depth 210 mm description Width 300 mm Height 1980 mm Depth 210 mm Embedding depth 210 mm Number of 18 mm 12 x 12 modules per row Electrical insulation Class II Additional information Can be combined side by side and one on top of Condition of use Indoor Provided equipment 2 x cable entry plate 1 x door Type of front cover Plain door

Complementary

Complementary		
Cable entry	Entry from the bottom or from the top	
Door type	Internal plain	
Number of locks	3	
Door opening side	Right or left	
Door opening angle	110°	
Enclosure mounting	Floor-standing	
Mounting support	Hollow wall Concrete	
9 mm pitches	288.0	
Total number of 18 mm modules	144.0	
[ln] rated current	400 A	
Locking options description	Sealable Keylock option	
Enclosure material	Enclosure: powder coated steel Door: powder coated steel	
Net weight	26.300 kg	
Colour	White (RAL 9016)	

Environment

IP degree of protection	IP44	
IK degree of protection	IK10	
Standards	IEC 61439	
	EN 62208	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	218 cm	
Package 1 Width	80 cm	
Package 1 Length	120 cm	
Package 1 Weight	35.3 kg	