

| Main | |
|------------------------------------|--|
| Range | Prisma |
| Product name | Prisma XS |
| Product or component type | Enclosure |
| Enclosure type | Empty enclosure |
| Enclosure/cubicle description | Wall-mounted enclosure depth 210 mm |
| Width | 550 mm |
| Height | 1100 mm |
| Depth | 210 mm |
| Embedding depth | 210 mm |
| Number of 18 mm modules per row | 14 x 12 |
| Electrical insulation class | Class II |
| Additional information | Can be combined side by side and one on top of another |
| Condition of use | Indoor |

4 x cable entry plate

1 x door Plain door

Complementary

| Complementary | | |
|-------------------------------|--|--|
| Cable entry | Entry from the bottom or from the top | |
| Door type | Internal plain | |
| Number of locks | 3 | |
| Door opening side | Right or left | |
| Door opening angle | 110° | |
| Enclosure mounting | Flush Surface Recessed | |
| Mounting support | Hollow wall Concrete | |
| 9 mm pitches | 336 | |
| Total number of 18 mm modules | 168 | |
| [In] rated current | 400 A | |
| Locking options description | Sealable Keylock option | |
| Enclosure material | Enclosure: powder coated steel Door: powder coated steel Inside enclosure: plastic | |
| Net weight | 16.500 kg | |
| Colour | White (RAL 9016) | |

Provided equipment

Type of front cover

Environment

| IP degree of protection | IP44 | |
|-------------------------|--|--|
| IK degree of protection | IK10 | |
| Standards | IEC 61439 DIN VDE 0603 part 1 EN 62208 | |
| | | |

Packing Units

| • | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 113 cm |
| Package 1 Width | 56 cm |
| Package 1 Length | 22 cm |
| Package 1 Weight | 19.05 kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 7 |
| Package 2 Height | 127 cm |
| Package 2 Width | 80 cm |
| Package 2 Length | 120 cm |
| Package 2 Weight | 145.35 kg |
| | |