ABWRS209Z14

Distribution enclosure with 4 meter panels, Prisma XS, wall-mounted, w/o door, IP30, (W)550mm x (H)1400mm x (D)210mm



Main	
Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Distribution enclosure with metering
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	550 mm
Height	1400 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	2 x 24
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	4 x cable entry plate 4 x metering plate 2 x DIN rail panel
Type of front cover	Without

Complementary

Entry from the bottom or from the top
Flush Surface Recessed
Hollow wall Concrete
96
48
63 A
Enclosure: powder coated steel Inside enclosure: plastic
24 kg
White (RAL 9016)

Environment

IP degree of protection	IP30	
IK degree of protection	IK10	
Standards	IEC 61439 EN 62208	

Packing Units

Unit Time of Dealiness 4	DOE.
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	143 cm
Package 1 Width	56 cm
Package 1 Length	22 cm
Package 1 Weight	25.3 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	127 cm
Package 2 Width	80 cm
Package 2 Length	147 cm
Package 2 Weight	166.8 kg