APO Dry Contact I/O Accessory







Overview

Presentation	UPS management accessory that provides two dry contact input and one relay output interface to APC UPS management offers with UIO ports such as the UPS Network Management Card (AP9641, AP9643) or Dry Contact I/O SmartSlot Card (AP9613).
Lead time	Usually in Stock

Main

Provided equipment	Cat 5 Ethernet cable User manual

Physical

		.3
Colour	Black	
Height	2.2 cm	-
Width	4.52 cm	
Depth	4.46 cm	
Net weight	0.05 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	

Conformance

Comomanco		
Standards	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-6	

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	03333 ft
Relative humidity	095 %
Ambient air temperature for storage	-1565 °C
Storage altitude	0.004572.00 m
Storage Relative Humidity	095 %

Packing Units

<u> </u>		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.300 cm	
Package 1 Width	25.400 cm	
Package 1 Length	12.700 cm	
Package 1 Weight	140.000 g	
Unit Type of Package 2	PAM	

Number of Units in Package 2	576	
Package 2 Height	123.000 cm	
Package 2 Width	120.000 cm	
Package 2 Length	100.000 cm	
Package 2 Weight	80.960 kg	

Offer Sustainability

Green Premium product
☑ REACh Declaration
Compliant EEU RoHS Declaration
Yes
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Energy efficient product
Take-back program available

Contractual warranty

Warranty	2 years repair or replace