



### Main

Range	PowerLogic
Product or component type	Current transformer
Electrical connection	Cable: 6.1 m600 V
[In] rated current	200 A

### Complementary

Product destination	BCPMSC
Current transformer type	Split core balance
Network frequency	50/60 Hz
Width	Internal: 32 mm External: 64 mm
Depth	39 mm
Height	Internal: 32 mm External: 71 mm

### Environment

Ambient air temperature for operation	0...60 °C
---------------------------------------	-----------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.81 cm
Package 1 Width	30.99 cm
Package 1 Length	38.71 cm
Package 1 Weight	522.73 g

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.