



### Main

Product range	Mureva BOX
Product type	Junction box
Quantity per package	5 pieces

### Complementary

Mounting	Surface
Cable entry	Grommets
Fixing mode	Clip-on: cover
Inner dimensions	105 x 65 x 55 mm
Number of cable entries	8 diameter: 20 mm
Material	ABS (acrylonitrile butadiene-styrene): body PP (polypropylene): cover SBS (styrene butadiene styrene): grommet
Electrical insulation class	Class II conforming to IEC 536
Height	61 mm
Width	125 mm
Depth	83 mm
Net weight	0.092 kg

### Environment

Operating temperature	-25...40 °C
IP-Class	IP55 conforming to IEC 60529
IK-Class	IK07 conforming to EN 50102
Glow wire temperature	650 °C
Standards	EN 60670 CE

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.7 cm
Package 1 Width	2.6 cm
Package 1 Length	6.2 cm
Package 1 Weight	92 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------