

EPDU1016B

APC Easy Rack PDU, Basic, 1U, 1 Phase,
3.7kW, 230V, 16A, 8 x C13 outlets, IEC60320
C20 inlet



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.50 m
Provided equipment	Installation guide Rack mounting brackets User manual Cable

Complementary

Input Voltage	200 V 208 V 230 V
Height	4.44 cm
Width	48.2 cm
Output Voltage	208 V 230 V
Depth	4.44 cm
Net weight	0.58 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE[RETURN]TÜV
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	8 cm
Package 1 Length	56 cm
Package 1 Weight	1.18 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------