## EVK8KN4PB40

Protection kit (tap-off unit, MCB/RCD), EVlink, mounting on Canalis KN trunking, for 22 kW charging station, 4P, 40 A



Main	
Range	EVlink
Product or component type	Tap-off unit
Range compatibility	Canalis KN busbar trunking EVlink EVlink parking EVlink EVlink Wallbox EVlink EVlink Wallbox Plus EVlink EVlink Smart Wallbox
Product compatibility	Canalis KN busbar trunkingplug-in
Nominal output power	22 kW

Complementary

Device application	Low power distribution
Protection device type	1.0 x miniature circuit breaker (MCB) - 4P - 40 A at 400 V - C curve 1.0 x residual current circuit breaker (RCCB) - 4P - 40 A at 400 V - 30 mAtype B- EV (Electric Vehicle)
Provided equipment	Miniature circuit breaker (MCB) Residual current device (RCD) Cable gland to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
[Uimp] rated impulse withstand voltage	4.6 kV
[Ui] rated insulation voltage	500 V
Network frequency	50/60 Hz
Electrical connection	Tunnel terminal - ISO50 25 mm² flexible Tunnel terminal - ISO50 25 mm² rigid
Door opening side	Right
Tap-off unit disconnection mode	By opening the door
Earthing system	TT TN-S IT
Colour	White (RAL 9001)
18 mm pitches	8
Width	344 mm
Depth	106 mm
Door opening size	432.5 mm
Height	165 mm

## Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Standards	IEC 61439-6
	IEC 61439-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.7 cm
Package 1 Width	34.6 cm
Package 1 Length	16.6 cm
Package 1 Weight	2.442 kg
Unit Type of Package 2	P12
Number of Units in Package 2	52
Package 2 Height	60 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	138.984 kg