ILM1001P11F0000

integrated servo motor - 2.5 Nm - 3000 rpm - keyed shaft - with brake





Main

Range of product	PacDrive 3
Product or component type	Servo motor integrated drive
Device short name	ILM

Complementary

[Us] rated supply voltage	250700 V	
Continuous stall current	1.8 A	
Continuous stall torque	2.5 N.m	
Peak stall torque	9.6 N.m	
Nominal output power	600 W	
Nominal torque	1.9 N.m	
Nominal speed	3000 rpm	
Maximum current Irms	7.4 A	
[ln] rated current	1.4 A	
Shaft end	Keyed	
Second shaft	Without second shaft end	
Shaft diameter	19 mm	
Shaft length	40 mm	
Key width	30 mm	
Feedback type	Absolute single turn SinCos Hiperface	
Speed feedback resolution	128 periods	
Holding brake	With	
Holding torque	5.5 N.m holding brake	
Mounting support	International standard flange	
Motor flange size	100 mm	
Torque constant	1.39 N.m/A at 120 °C	
Back emf constant	90 V/krpm at 20 °C	
Number of motor poles	8	
Rotor inertia	2.1 kg.cm ²	
Stator resistance	9.8 Ohm at 20 °C for Ph/Ph	
	6.82 Ohm at 120 °C for Ph/N	
Stator inductance	45.7 MH at 20 °C for Ph/Ph 22.85 mH at 120 °C for Ph/N	
Maximum radial force Fr	900 N at 1000 rpm 720 N at 2000 rpm	
	630 N at 3000 rpm	
Maximum axial force Fa	0.2 x Fr	
Type of cooling	Natural convection	
Length	243 mm	

Number of motor stacks	1
Centring collar diameter	95 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Circle diameter of the mounting holes	115 mm
Net weight	5.7 kg

Environment

IP degree of protection	IP54	
ii dogree or protoction		

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	26.0 cm	
Package 1 Width	20.0 cm	
Package 1 Length	59.0 cm	
Package 1 Weight	6.33 kg	

Offer Sustainability

onor odotamasmy		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
PVC free	Yes	