KBC1S

Cam switch operating head, Harmony K, \tilde{A}^{\sim} 22mm, plastic, 45x45mm plate, metallic legend, key operated, 601 A



Main

Range of product	Harmony Series K
Product or component type	Cam switch operating head
Component name	KBC
Product compatibility	Front mounting bodies 12 and 20 A by Ø 22 mm hole
Cam switch head type	With front plate 45 x 45 mm
Type of operator	Key 601A
Rotary handle padlocking	Without
Presentation of legend	With metallic legend
Switching angle	45 ° 90 °

Complementary

Mechanical durability	1000000 cycles	
CAD overall width	45 mm	
CAD overall height	45 mm	
CAD overall depth	69 mm	
Net weight	0.063 kg	
Compatibility code	KBC	

Environment

Protective treatment	TC	
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4070 °C	
Shock resistance	30 gn conforming to IEC 68-2-27	
Vibration resistance	5 gn conforming to IEC 68-2-6 (f = 10150 Hz)	
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.6 cm	
Package 1 Width	6.6 cm	
Package 1 Length	8.0 cm	
Package 1 Weight	69.0 g	
Unit Type of Package 2	S03	
Number of Units in Package 2	60	
Package 2 Height	30.0 cm	
Package 2 Width	30.0 cm	
Package 2 Length	40.0 cm	
Package 2 Weight	4.673 kg	

Offer Sustainability

REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
₫Yes

Contractual warranty

Warranty	18 months
----------	-----------