
# KRB0190CF12 CANALIS KR 12X0190 FIRE BARRIER S120 / CF





#### Main Range Canalis Product name KR Product or component Busbar cover type Busbar description Fire barrier Device short name KRB Range compatibility Canalis KR KRA[RETURN]Canalis KR KRC Device application Feeder length [le] rated operational 1600 A with aluminium 2000 A with copper current

3L + N + PE 550 mm

Complementary

Fire protection accessory	
1000 V	
Surface mounted	
EAC[RETURN]ATEX[RETURN]CE	
IEC 61439-6	
20 mm	
230 mm	
160 mm	
Grey (RAL 7030)	
1	
	1000 V Surface mounted EAC[RETURN]ATEX[RETURN]CE IEC 61439-6 20 mm 230 mm 160 mm

Busbar trunking polarity

Length

#### Environment

IP degree of protection	IP68 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Pollution degree	3	
Fire resistance	0 °C 120 min conforming to DIN 4102-9	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	19.0 cm	
Package 1 Width	12.0 cm	
Package 1 Length	70.0 cm	
Package 1 Weight	7.72 kg	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	<sup>™</sup> End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Halogen content performance	Halogen free product	