



Main

Product or component type	Phase barrier
Accessory / separate part category	Installation accessories
Poles description	3P
Quantity per set	Set of 2

Complementary

Product compatibility	LC1G115...225 LC1G265...500 LC1G630...800
Height	2 mm
Width	115.5 mm
Depth	122 mm
Net weight	0.1 kg
[Ui] rated insulation voltage	1000 V

Environment

Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-40...60 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating 5000 m with derating factor
Standards	EN/IEC 60947-1 UL 60947-1 CSA C22.2 No 60947-1 GB/T 14048
Product certifications	ABS[RETURN]BV[RETURN]CB[RETURN]CCC[RETURN]CCS[RETURN]CUL[RETURN]DNV[RETURN]GL[RETURN]IEC[RETURN]JKA[RETURN]LROS (Lloyds register of shipping) [RETURN]RINA[RETURN]RMRoS

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	115.5 cm
Package 1 Length	122.0 cm
Package 1 Weight	150.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm

Package 2 Length	40.0 cm
Package 2 Weight	750.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product