



### Main

Range	TeSys
Device short name	LA9G
Product or component type	Switch module
Quantity per set	Set of 4

### Complementary

Product compatibility	LC1G265...330
Accessory / separate part type	Kit
Maximum [I <sub>e</sub> ] rated operational current	440 A AC-1 <= 440 V at 40 °C
Poles description	4P
Connections - terminals	Bolted connection

### Environment

Pollution degree	3 conforming to IEC 60947-1
Operating altitude	3000 m without power derating 5000 m with derating factor
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 GB/T 14048.4
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	26.0 cm
Package 1 Length	21.0 cm
Package 1 Weight	4.5 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.6 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product





