



### Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out Modular
Installed device	Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A

### Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Connection position	Direct connection
Number of horizontal rows	3
9 mm pitches	48
Number of 18 mm modules per row	24
Number of vertical modules [50 mm]	8
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	400 mm
Width	500 mm
Net weight	1.24 kg
Quantity per set	Set of 1
Functional unit	600 mm PrismaSeT G floor-standing enclosure Acti 9 modular device <= 40 A fixed 48 direct 8 600 mm PrismaSeT G wall-mounted enclosure Acti 9 modular device <= 40 A fixed 48 direct 8 650 mm 400 mm PrismaSeT P cubicle Acti 9 modular device <= 40 A fixed 48 direct 8 600 mm PrismaSeT G floor-standing enclosure Multi9 modular device <= 40 A fixed 48 direct 8 600 mm PrismaSeT G wall-mounted enclosure Multi9 modular device <= 40 A fixed 48 direct 8 650 mm 400 mm PrismaSeT P cubicle Multi9 modular device <= 40 A fixed 48 direct 8

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	41.5 cm
Package 1 Length	51.5 cm
Package 1 Weight	1.27 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	11 cm
Package 2 Width	52 cm
Package 2 Length	53 cm
Package 2 Weight	8.227 kg
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	57 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	77 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product