



### Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Plain
Installed device	Power meters: kilowatt-hour meters - vertical installation Connection Altistart: ATS01N
Poles description	3 x 2P: mounting plate support: kilowatt-hour meters vertical installation 2 x 4P: mounting plate support: kilowatt-hour meters vertical installation

### Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Number of vertical modules [50 mm]	6
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	300 mm
Width	500 mm
Net weight	1.22 kg
Quantity per set	Set of 1
Functional unit	600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 2P 3 6 600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 2P 3 6 600 mm PrismaSeT G floor-standing enclosure connection 2 6 600 mm PrismaSeT G wall-mounted enclosure connection 2 6 650 mm 400 mm PrismaSeT P cubicle connection 2 6 600 mm PrismaSeT G floor-standing enclosure power meters kilowatt-hour meters vertical 4P 2 6 600 mm PrismaSeT G wall-mounted enclosure power meters kilowatt-hour meters vertical 4P 2 6 650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 2P 3 6 650 mm 400 mm PrismaSeT P cubicle power meters kilowatt-hour meters vertical 4P 2 6 600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 9 6 600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 9 6 600 mm PrismaSeT G floor-standing enclosure Altistart ATS01N 2 6 600 mm PrismaSeT G wall-mounted enclosure Altistart ATS01N 2 6 650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 9 6 650 mm 400 mm PrismaSeT P cubicle Altistart ATS01N 2 6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	31.0 cm
Package 1 Length	51.0 cm
Package 1 Weight	1.235 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	16.5 cm
Package 2 Width	32.5 cm
Package 2 Length	52.0 cm
Package 2 Weight	12.656 kg
Unit Type of Package 3	P12
Number of Units in Package 3	180
Package 3 Height	78.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	239.5 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product