
LVS04488

Connection, Linergy LGY, for NS, 4P, 1600A, vertical fixed





Main	
Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Connection
Product name	PrismaSeT PrismaSeT P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Complementary		
Cubicle-device connection	Linergy busbar	
Poles description	4P	
Installation description	Cubicle - width 650 mm	
Cubicle depth	400 mm: front 400 + 400 mm: rear	
Installed device	ComPact: fixed NS1600 - control: toggle vertical installation ComPact: fixed NS1600 - control: direct front rotary handle vertical installation ComPact: fixed NS1600 - control: motor mechanism vertical installation	
[le] rated operational current	1600 A	
Busbar cross section	80 x 10 mm	
Height	150 mm	
Width	550 mm	
Depth	300 mm	
Net weight	18.84 kg	
Quantity per set	Set of 1	
Functional unit	650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed toggle vertical 4P 1 rear connection on Canalis 16 650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed direct front rotary handle vertical 4P 1 rear connection on Canalis 16 650 mm 400 mm PrismaSeT P cubicle ComPact NS1600 fixed toggle vertical 4P 1 front connection on adaptor 14 650 mm 400 mm PrismaSeT P cubicle ComPact NS1600 fixed direct front rotary handle vertical 4P 1 front connection on adaptor 14 650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16 650 mm 400 mm PrismaSeT P cubicle ComPact NS1600 fixed motor mechanism vertical 4P 1 front connection on adaptor 14	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.0 cm	
Package 1 Width	12.0 cm	
Package 1 Length	54.0 cm	
Package 1 Weight	18.33 kg	
Unit Type of Package 2	P12	
Number of Units in Package 2	12	

Package 2 Height	27.0 cm	
Package 2 Width	80.0 cm	
Package 2 Length	120.0 cm	
Package 2 Weight	240.0 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product