LVS04565

Profile busbar, Linergy LGYE, 2000A, for a horizontal installation, L2000mm





Main

Linergy
Linergy
Profile busbar
Linergy LGYE
PrismaSeT PrismaSeT P enclosure
Busbar accessory
Linergy
Set of 1

Complementary

Installation direction	Horizontal, operating position: top	
	Horizontal, operating position: bottom	
Installation description	Cubicle - width 650 mm	
	Cubicle - width 650 + 150 mm	
	Cubicle duct - width 300 mm	
	Cubicle duct - width 400 mm	
[Ui] rated insulation voltage	1000 V	
[Uimp] rated impulse withstand voltage	12 kV (degree of pollution: 3)	
[le] rated operational current	2000 A	
[lcw] rated short-time withstand current	60 KA (1 s) for 2 supports (horizontal position)	
	85 KA (1 s) for 3 supports (horizontal position)	
	100 kA (1 s) for 4 supports (horizontal position)	
Permissible current	2000 A at 35 °C: <= IP31	
	1650 A at 35 °C: > IP31	
Length	2000 mm	
Height	150 mm	
Width	100 mm	
Depth	31 mm	
Net weight	5.93 kg	
Colour	Natural	
Type of busbar connection	Single t-slot	
Connection pitch	Free connection position	

Environment

Standards	IEC 61439-2 IEC 61439-1	
Product certifications	ASTA	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.5 cm	
Package 1 Width	10.8 cm	
Package 1 Length	210.0 cm	
Package 1 Weight	7.067 kg	

Unit Type of Package 2	PAL
Number of Units in Package 2	48
Package 2 Height	40.0 cm
Package 2 Width	120.0 cm
Package 2 Length	202.0 cm
Package 2 Weight	360.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product