



### Main

|                                    |                                  |
|------------------------------------|----------------------------------|
| Range                              | PrismaSeT                        |
| Range of product                   | PrismaSeT P                      |
| Product or component type          | Interface and connection Canalis |
| Product name                       | PrismaSeT PrismaSeT P enclosure  |
| Accessory / separate part category | Interface accessory              |
| Standards                          | IEC 61439-2<br>IEC 61439-1       |
| Product certifications             | ASTA                             |

### Complementary

|                                |  |
|--------------------------------|--|
| Cubicle-device connection      | KT with Canalis  |
| Poles description              | 4P   |
| Installation description       | Cubicle - width 650 mm   |
| Cubicle depth                  | 600 mm: front<br>600 + 400 mm: rear  |
| Installed device               | Masterpact: drawout NW08...16 - control: toggle vertical installation<br>Masterpact: fixed NW08...16 - control: toggle vertical installation   |
| [Ie] rated operational current | 1600 A   |
| Colour                         | Natural  |
| Height                         | 350 mm   |
| Width                          | 575 mm   |
| Depth                          | 420 mm   |
| Net weight                     | 49.9 kg  |
| Quantity per set               | Set of 1   |
| Functional unit                | 650 mm 600 mm PrismaSeT P cubicle Masterpact NW08...16 drawout toggle vertical 4P 1 front connection on Canalis 27<br>650 mm 1000 mm PrismaSeT P cubicle Masterpact NW08...16 drawout toggle vertical 4P 1 rear connection on Canalis 17<br>650 mm 600 mm PrismaSeT P cubicle Masterpact NW08...16 fixed toggle vertical 4P 1 front connection on Canalis 27<br>650 mm 1000 mm PrismaSeT P cubicle Masterpact NW08...16 fixed toggle vertical 4P 1 rear connection on Canalis 16 |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 43.000 cm |
| Package 1 Width              | 40.000 cm |
| Package 1 Length             | 62.000 cm |
| Package 1 Weight             | 45.500 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product                    |
| REACH Regulation           | <a href="#">REACH Declaration</a>        |
| EU RoHS Directive          | Compliant with Exemptions                |
| Mercury free               | Yes                                      |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>                      |
| Circularity Profile        | No need of specific recycling operations |