LVS08336

Door, PrismaSeT G, transparent with frame, 23M, W600, IP55, white, RAL 9003





Main

| Range | PrismaSeT |
|---------------------------|---|
| Range of product | PrismaSeT G |
| Product or component type | Door |
| Range compatibility | PrismaSeT PrismaSeT G enclosure |
| Provided equipment | Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 2 hinge |
| Type of door | Transparent |
| IP degree of protection | IP55 |

Complementary

| Installation description | Wall-mounted enclosure - width 600 mm | |
|------------------------------------|---------------------------------------|--|
| | Extension enclosure - width 600 mm | |
| Door opening side | Reversible | |
| Number of locks | 3 | |
| Door opening angle | 180 ° | |
| Number of vertical modules [50 mm] | 23 | |
| Enclosure material | Glass | |
| | Treated sheet steel | |
| Quantity per set | Set of 1 | |
| Height | 1250 mm | |
| Width | 600 mm | |
| Depth | 26 mm | |
| Net weight | 18.26 kg | |
| Material | Glass | |
| Surface finish | Textured | |
| | Matt | |
| Colour | White (RAL 9003) | |

Environment

| IK degree of protection | IK10 conforming to EN/IEC 62262 |
|-------------------------|--|
| Standards | IEC 61439-2 IEC 61439-1 |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 7.5 cm | |
| Package 1 Width | 60.0 cm | |
| Package 1 Length | 124.0 cm | |
| Package 1 Weight | 18.2 kg | |
| Unit Type of Package 2 | P12 | |
| Number of Units in Package 2 | 10 | |
| Package 2 Height | 83.0 cm | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| Package 2 Width | 80.0 cm |
|------------------|----------|
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 194.0 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | ☑ REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Circularity Profile | No need of specific recycling operations |