

Product data sheet

Characteristics

LVS08880

Roof plate, PrismaSeT G, for enclosure, W600mm, IP30, metal plate with plastic gland plates, white, RAL 9003



Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Roof plate
Range compatibility	PrismaSeT PrismaSeT G enclosure
Device application	Low voltage electrical distribution
Enclosure type	Metal enclosure Indoor enclosure
Installation description	Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 600 mm
Provided equipment	1 gland plate 1 plate with cut-outs
Standards	IEC 61439-1 for enclosure IEC 61439-2 for enclosure
Product certifications	ASTA

Complementary

Material	Treated sheet steel Plastic
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	590 mm
Height	35 mm
Depth	195 mm
Net weight	0.96 kg
Quantity per set	Set of 1

Environment

IP degree of protection	IP30 for enclosure
IK degree of protection	IK08

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	20.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	1.001 kg
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Height	42.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	52.040 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes