LX1G4QKUEN

Control module, TeSys Giga, 100-250V AC/DC, for LC1G115-225/4P standard version





Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1G
Poles description	4P
Range compatibility	TeSys G LX1G contactor coil
Product compatibility	LC1G115225
[Uc] control circuit voltage	100250 V AC/DC 50/60 Hz
Operating time	2035 ms opening 4055 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	600 cyc/mn 60 °C

Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	Operational: 0.81.1 Uc (at 60 °C) Drop-out: 00.45 Uc (at 60 °C)
Connections - terminals	Control circuit: push-in termination 1 cable(s) 0.22.5 mm² solid stranded without cable end sleeve AWG 26AWG 12 Control circuit: push-in termination 1 cable(s) 0.252.5 mm² flexible with cable end sleeve AWG 24AWG 14 Control circuit: push-in termination 2 cable(s) 0.51.0 mm² rigid or stranded with cable end sleeve AWG 20AWG 18
Inrush power in VA	485 VA at 240 V AC, 50 Hz
Inrush power in W	365.0 W DC
Hold-in power consumption in VA	9.4 VA at 240 V AC, 50 Hz
Hold-in power consumption in W	5.2 W for DC network

Environment

LIIVII OIIIITEIR	ID00 ('
IP degree of protection	IP20 conforming to IEC 60529
Operating altitude	3000 m without derating
	5000 m with derating factor
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1
	Emission tests criteria A conforming to IEC 60947-4-1
	Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3
	Voltage dips and interruptions immunity test conforming to SEMI F47
Standards	EN/IEC 60947-4-1
	UL 60947-4-1A
	CSA C22.2 No 60947-4-1
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-6080 °C
Permissible ambient air temperature around the	-4070 °C at Uc
device	
Height	144.5 mm
Width	140.7 mm
Depth	94.0 mm
Quantity per set	1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.0 cm
Package 1 Width	22.0 cm
Package 1 Length	22.0 cm
Package 1 Weight	1.6 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Product data sheet Maßzeichnungen

LX1G4QKUEN

Product data sheet Anschlüsse und Schema

LX1G4QKUEN

Product data sheet Leistungskurven

LX1G4QKUEN