Product data sheet Characteristics

LXMRL03S0000

collaborative robot, Lexium Cobot, maximum payload 3kg





Main

Range of product	Lexium Cobot
Product or component type	Collaborative robot
Maximum payload	3 kg
Operating radius	626 mm
Positioning accuracy	+/- 0.02 mm
Degree of freedom	6
Programming	Graphical drag & drop
Teach-in device	Ipad ios app Android app

Complementary

Complementary	
Maximum speed	180°/S joint 1 +/- 360° 180°/S joint 2 -85, +265° 180°/S joint 3 +/- 175° 220°/S joint 4 -85, +265° 220°/S joint 5 +/- 360° 220°/s joint 6 +/- 360°
Rated voltage	24 V
Digital input number	2
Digital output number	2
Analogue input number	1
Maximum power consumption in W	150 W
Mounting position	Any position
Screw type	M8
Standards	GB 11291.1:2011 EN/ISO 10218-1:2011 EN 60204-1:2018 EN/ISO 12100:2010 EN/ISO 13849-1:2015 EN 61000-6-2:2005 EN 61000-6-4:2007+A1:2011 ISO 13849-1:2015 ISO 13849-2:2012 ISO 14644-1 ISO 9001:2015 UL 1740 ANSI/RIA R15.06 CAN/CSA Z434 NFPA 79 CAN/CSA C22.2 No. 24 REACH R0HS
Marking	CE KC TÜV
Material	Aluminium
Base diameter	129 mm
Cable length	6 m
Net weight	12 kg

Environmental

IP degree of protection	IP54
Ambient air temperature for operation	050 °C

Packing Units

1
1
37 cm
42 cm
49 cm
14.6 kg
P06
2
75 cm
60 cm
80 cm
37.7 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile