MTN6215-5910

Thermostat with TFT display, KNX, room, black, System Design





Main

Range	Merten
Aesthetic name	D-Life System Design
Product or component type	Thermostat
Device presentation	Mechanism with fixing frame and central plate
Device application	Room
Colour tint	Black

Complementary

Electronic	Complementary		
Fixing mode By 2 screws Push Function available Function available Cleaning mode Background lighting Controller type: 2-step controller Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams 32 functions room controller Controller type: continuous-action PI control Scene retrieval Output: switching ON/OFF Switching, toggling, dimming All functions are displayed on a touch screen Setpoint adjustment Switch-on behaviour of the user interface Integrated room temperature controller Scene saving Output: continuous in the range 0 to 100% Blind control Screen saver 8-bit linear regulator Operating modes Controller type: switching PI control (PWM) Gesture function: the device recognises a gesture Valve protection function Proximity function: for the display and the start screen Pulse edges with 2-byte telegrams Fan control Display type Colour TFT display Control type X touch screen Mechanical robustness With optional anti-theft or dismantling protection Material Plastic Height 71 mm Width 71 mm Width 71 mm Depth	Technology type	Electronic	
Device mounting Flush Function available Signal function Cleaning mode Background lighting Controller type: 2-step controller Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams 32 functions room controller Controller type: continuous-action PI control Scene retrieval Output: switching ON/OFF Switching, toggling, dimming All functions are displayed on a touch screen Setpoint adjustment Switch-on behaviour of the user interface Integrated room temperature controller Scene saving Output: continuous in the range 0 to 100% Blind control Screen saver 8-bit linear regulator Operating modes Controller type: switching PI control (PWM) Gesture function: the device recognises a gesture Valve protection function Proximity function: for the display and the start screen Pulse edges with 2-byte telegrams Fan control Display type Colour TFT display Control type X touch screen Mechanical robustness With optional anti-theft or dismantling protection Material Plastic Height 71 mm Width 71 mm Width 71 mm Depth	Bus type	KNX	
Function available Signal function Cleaning mode Background lighting Controller type: 2-step controller Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams 32 functions room controller Controller type: continuous-action PI control Scene retrieval Output: switching ON/OFF Switching, toggling, dimming All functions are displayed on a touch screen Setpoint adjustment Switch-no hehaviour of the user interface Integrated room temperature controller Scene saving Output: continuous in the range 0 to 100% Blind control Screen saver 8-bit linear regulator Operating modes Controller type: switching PI control (PWM) Gesture function: the device recognises a gesture Valve protection function Proximity function: for the display and the start screen Pulse edges with 2-byte telegrams Fan control Display type Colour TFT display Control type X touch screen Mechanical robustness With optional anti-theft or dismantling protection Material Plastic Height 71 mm Width 71 mm Use the service of the control of the service of the serv	Fixing mode	By 2 screws	
Cleaning mode Background lighting Controller type: 2-step controller Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams 32 functions room controller Controller type: continuous-action PI control Scene retrieval Output: switching ON/OFF Switching, toggling, dimming All functions are displayed on a touch screen Setpoint adjustment Switch-on behaviour of the user interface Integrated room temperature controller Scene saving Output: continuous in the range 0 to 100% Blind control Screen saver 8-bit linear regulator Operating modes Controller type: switching PI control (PWM) Gesture function: the device recognises a gesture Valve protection function Proximity function: for the display and the start screen Pulse edges with 2-byte telegrams Fan control Display type Colour TFT display Control type X touch screen Mechanical robustness With optional anti-theft or dismantling protection Material Plastic Height 71 mm Width 71 mm Depth 30 mm	Device mounting	Flush	
Control type X touch screen Mechanical robustness With optional anti-theft or dismantling protection Material Plastic Height 71 mm Width 71 mm Depth 30 mm		Cleaning mode Background lighting Controller type: 2-step controller Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams 32 functions room controller Controller type: continuous-action PI control Scene retrieval Output: switching ON/OFF Switching, toggling, dimming All functions are displayed on a touch screen Setpoint adjustment Switch-on behaviour of the user interface Integrated room temperature controller Scene saving Output: continuous in the range 0 to 100% Blind control Screen saver 8-bit linear regulator Operating modes Controller type: switching PI control (PWM) Gesture function: the device recognises a gesture Valve protection function Proximity function: for the display and the start screen Pulse edges with 2-byte telegrams Fan control	
Mechanical robustnessWith optional anti-theft or dismantling protectionMaterialPlasticHeight71 mmWidth71 mmDepth30 mm			
Material Plastic Height 71 mm Width 71 mm Depth 30 mm	Control type	*****	
Height 71 mm Width 71 mm Depth 30 mm	Mechanical robustness	With optional anti-theft or dismantling protection	
Width 71 mm Depth 30 mm	Material	Plastic	
Depth 30 mm	Height	71 mm	
	Width	71 mm	
Main colour tint Black	Depth	30 mm	
	Main colour tint	Black	

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.700 cm
Package 1 Width	7.600 cm
Package 1 Length	7.700 cm
Package 1 Weight	102.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	19.500 cm
Package 2 Width	30.300 cm
Package 2 Length	40.500 cm
Package 2 Weight	5.576 kg

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant with Exemptions	
Yes	
☐ China RoHS Declaration	
€Yes	
Product Environmental Profile	
End Of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	