MTN639126

Thermoelectric valve drive 24 V, polar white





Main

Range of product	KNX	
Product or component type	Thermoelectric valve drive	

Complementary

[Ue] rated operational voltage	24 V

Environment

LIMIOIIIICII		
IP degree of protection	IP54	

Packing Units

I acking onits	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	8.400 cm
Package 1 Length	10.600 cm
Package 1 Weight	140.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	35
Package 2 Height	19.600 cm
Package 2 Width	30.700 cm
Package 2 Length	40.800 cm
Package 2 Weight	5.306 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	[™] End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Warranty 18 months