NSYCEA22E

ClimaSys Exchanger air-air 22W/K side mounted without T





Main	
Range	ClimaSys
Product name	ClimaSys CE
Product or component type	Air-air exchanger
Mounting type	Sides of enclosure
Cooling power	22 W power is obtained by multiplying specific power by DeltaT (Tex.t-Tint.)

Complementary

External circuit: 280 m3/h Internal circuit: 280 m3/h	
Without	
555 °C outside the enclosure:	
Air	
230 V 50/60 Hz	
0.5 A	
72 W	
External: 413 mm	
External: 189 mm	
External : 149 mm	
7 kg	
59 dB conforming to EN/ISO 3746	
Thermal protection: T 1 A	
Steel	
Grey (RAL 7035)	
	Internal circuit: 280 m3/h Without 555 °C outside the enclosure: Air 230 V 50/60 Hz 0.5 A 72 W External: 413 mm External: 189 mm External: 149 mm 7 kg 59 dB conforming to EN/ISO 3746 Thermal protection: T 1 A Steel

Environment

IP degree of protection	IP55 (internal IP) IP2XC (external IP)	
Product certifications	CE	
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive 2006/42/EC - machinery	
Standards	EN 60335-1 EN 60204-1 EN 60335-2-40 EN/ISO 12100	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	21.0 cm	
Package 1 Width	23.0 cm	
Package 1 Length	53.0 cm	
Package 1 Length	53.0 cm	_

Package 1 Weight	7.25 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	70.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	112.0 kg

Offer Sustainability

onor ouclamacing	
Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins