NSYCU2K3P4RUL

ClimaSys standard cooling unit roof of enclosure - 2050W at 400 V





Main

Range	ClimaSys
Product name	CU
Product or component type	Cooling unit
Mounting type	Roof of enclosure
Installation	Indoor roof
Product destination	For enclosure
Mounting mode	By screws
Supply Voltage	460 V AC at 60 Hz, 3 phases
Rated Power	2300 W
Cooling power	6990 Btu/H 60 Hz L35-L35 5320 Btu/h 60 Hz L35-L50

Complementary

Height	415 mm	
Width	567 mm	
Depth	401 mm	
[In] rated current	1.9 A	
Inrush current	10 A	
Power consumption in W	990 W at 60 Hz, L35-L35 1190 W at 60 Hz, L35-L50	
Energy efficiency ratio	2.1	
Control type	Electronic controller	
Temperature setting range	2045 °C	
Ambient air temperature for operation	2045 °C outside the enclosure: 45 °C maximum: 2045 °C inside the enclosure:	
Noise level	65 dB	
Pressure	25 bar	
Flow rate	External circuit: 1820 m3/h at 60 Hz Internal circuit: 1050 m3/h at 60 Hz	
Net weight	52 kg	
Cooling gas type	R134a (0.55 kg)	
Type of filter	Optional external circuit filter	
Protection type	Thermal protection: T 6 A Short-circuit protection (magnetic):	
Material	Steel	
Colour	Grey (RAL 7035)	

Environment

Product certifications	UL
Standards	DIN 3168
IP degree of protection	IP34 conforming to IEC 60529 (on the external circuit) IP54 conforming to IEC 60529 (on the internal circuit)

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.1 cm
Package 1 Width	41.5 cm
Package 1 Length	56.7 cm
Package 1 Weight	52.0 kg
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	63.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	234.4 kg

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
₽¥Yes
Product Environmental Profile
End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins