Product data sheet Characteristics

NSYCU3K2DG

Side Connected Cooling Unit, Climasys CU, 3200W, 230V, 50/60Hz, IP55



| Main | |
|---------------------------|--|
| Range | ClimaSys |
| Product name | CU |
| Product or component type | Cooling unit |
| Mounting type | Side |
| Installation | Indoor side |
| Product destination | For enclosure |
| Mounting mode | By screws |
| Supply Voltage | 230 V AC at 50/60 Hz, 1 phase |
| Rated Power | 3200 W |
| Cooling power | 3200 W 50/60 Hz L35-L35 2500 W 50/60 Hz L35-L50 |

Complementary

| Height | 1300 mm |
|---------------------------------------|---|
| Width | 490 mm |
| Depth | 250 mm |
| [In] rated current | 9.0 A |
| Inrush current | 30 A |
| Power consumption in W | 1200 W at 50/60 Hz, L35-L35 1400 W at 50/60 Hz, L35-L50 |
| Energy efficiency ratio | 2.6 |
| Control type | Electronic controller |
| Temperature setting range | 2050 °C at 50/60 Hz |
| Ambient air temperature for operation | 2050 °C at 50/60 Hz inside the enclosure: 555 °C at 50/60 Hz outside the enclosure: |
| Noise level | 72 dB |
| Pressure | 32 bar |
| Flow rate | Internal circuit: 1200 m3/h at 50/60 Hz External circuit: 1400 m3/h at 50/60 Hz |
| Net weight | 59.6 kg |
| Cooling gas type | R134a (0.482 kg) |
| Type of filter | Optional external circuit filter |
| Protection type | Circuit breaker protection: miniature circuit breaker (MCB) |
| Protection type | Thermal protection: T 15 A Short-circuit protection (magnetic): |
| Material | Steel |
| Colour | Grey (RAL 7035) |

Environment

| Product certifications | UL[RETURN]IEC | |
|-------------------------|--|--|
| Directives | 2006/42/EC - machinery 2014/30/EU - electromagnetic compatibility | |
| | 2011/65/EU - RoHS | |
| Standards | EN/ISO 12100 | |
| | EN 60335-1 | |
| | EN 60335-2-40 | |
| | EN 61000-3-2 | |
| | EN 61000-3-3 | |
| | EN 61000-6-2 | |
| | EN 61000-6-3 | |
| | EN/IEC 63000:2018 | |
| | EN 14511 | |
| IP degree of protection | IP55 conforming to IEC 60529 (on the internal circuit) | |
| | IP24 conforming to IEC 60529 (on the external circuit) | |

Packing Units

| H-ST (Dl 4 | DOE |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 144 cm |
| Package 1 Width | 52 cm |
| Package 1 Length | 27.5 cm |
| Package 1 Weight | 64.6 kg |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 158.4 cm |
| Package 2 Width | 120 cm |
| Package 2 Length | 80 cm |
| Package 2 Weight | 154.2 kg |
| | |

Offer Sustainability

| REACh Declaration |
|---|
| Yes |
| Compliant EEU RoHS Declaration |
| China RoHS Declaration |
| €Yes |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| |