

# Product data sheet

## Characteristics

# PFXYP6MPR23P2

Expansion option, PS6000, 2 x D-Sub 9 pin plug connector, 2,400...115,200 bps



### Main

Range of product	PS6000
Product or component type	Serial line interface
Accessory / separate part category	Connection accessory

### Complementary

Integrated connection type	Mini PCIe with 2 male SUB-D 9 RS232C, transmission rate: 2400...115200 bps
Range compatibility	PS6000

### Environment

Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-30...70 °C
Relative humidity	10...90 % non-condensing

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	11.0 cm
Package 1 Length	14.0 cm
Package 1 Weight	200.0 g

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

### Contractual warranty

Warranty	24 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.