R9H10735

Modular enclosure, Resi9 KV, surface, 1x12 modules, 1 earth terminal block, plain door



Main	
Range	Resi9
Product name	Resi9 KV
Product or component type	Enclosure
Enclosure type	Modular enclosure
Width	300 mm
Height	245 mm
Depth	106 mm
Nb of 18 mm modules per row	12
Nb of horizontal rows	1
Provided equipment	1 x enclosure 1 x door 1 x terminal block 1 x identification label 1 x DIN rail
Type of door	Plain

Complementary

Enclosure mounting	Surface	
9 mm pitches	24	
Total number of 18 mm modules	12.0	
[In] rated current	63 A	
Number of terminal blocks	1 earth	
Distribution block outgoers	3 x 2.525 mm² for earth (screw connection) 14 x 1.54 mm² for earth (screwless connection)	
Enclosure material	Enclosure: self-extinguishing plastic Door: powder coated steel	
Colour	White (RAL 9016)	

Environment

IK degree of protection IK07 Overvoltage category II Ambient air temperature for operation -2035 °C		
IK degree of protection IK07 Overvoltage category II Ambient air temperature for operation -2035 °C Ambient air temperature for storage -2055 °C	Fire resistance	750 °C
Overvoltage category II Ambient air temperature for operation -2035 °C Ambient air temperature for storage -2055 °C	IP degree of protection	IP30
Ambient air temperature for operation -2035 °C Ambient air temperature for storage -2055 °C	IK degree of protection	IK07
Ambient air temperature for storage -2055 °C	Overvoltage category	II
	Ambient air temperature for operation	-2035 °C
Standards DIN EN 60670-24	Ambient air temperature for storage	-2055 °C
	Standards	DIN EN 60670-24

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.500 cm	
Package 1 Width	26.000 cm	
Package 1 Length	30.500 cm	
Package 1 Weight	1.650 kg	
Unit Type of Package 2	P12	
Number of Units in Package 2	90	
Package 2 Height	120.000 cm	

Package 2 Width	80.000 cm	
Package 2 Length	120.000 cm	
Package 2 Weight	157.500 kg	

Offer Sustainability

EU RoHS Directive	Under investigation