# RF-RCVR-433

# Security Expert Wireless 433MHz Receiver



#### Main

Range	EcoStruxure Security Expert
Device application	Building automation systems Remote security system Apartment complex access Vehicular gate operation
Product or component type	Wireless receiver

#### Complementary

Range compatibility	EcoStruxure Security Expert controller EcoStruxure Security Expert wireless transmitter	
[Ue] rated operational voltage	12 V DC	
[le] rated operational current	55 mA	
Type of receiver	Synthesized PLL	
Transmission frequency	433.92 MHz	
Operating distance	100 m in free field 200 m maximum	
Emission power	58 mW	
Emission power	100 mW	
Modulation technique	AM/ASK	
Receiver sensitivity	- 121 dBm	
Operating mode	RS232 system Wiegand system Standalone PGM control	
Storage capacity	600 ID (standalone)	
Input impedance	50 Ohm	
Output type	4 xopen collector NPN output 1 xform C relay	
Contacts type and composition	NO/NC programmable	
Length	73 mm	
Width	50 mm	
Height	26.5 mm	
Net weight	56 g	

#### Environment

Ambient air temperature for operation	-2070 °C	
Standards	ICES-003: class A	
	FCC CFR 47 part 15: class A CAN/ICES-003: class A	
	NMB: class A	
	NIVID. Class A	
Product certifications	CE[RETURN]ACMA[RETURN]AS/NZS	
Quality labels	RCM	
Directives	2014/35/EU - low voltage directive	
	2014/30/EU - electromagnetic compatibility	

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	13.2 cm	
Package 1 Width	3.7 cm	
Package 1 Length	15.7 cm	
Package 1 Weight	110.0 g	

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration