SLABXXX

SmartX Temperature Sensor, Resistive 10K Type 3 Thermistor, Blank, with Optimum Black Cover



Main	
Product or component type	Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	24 mm
Height	115 mm
Width	85 mm
Standards	UL 916 FCC part 15 class B
Colour	Black
Ambient air temperature for operation	050 °C
Relative humidity	095 %
Sensor type	10 kOhm T3 thermistor
Surface finish	Glossy
Product name	SmartX Living Space Sensor
Range	SpaceLogic

Complementary

Device presentation	Complete product	
Connections - terminals	Screw - 2 cable(s) (AWG 24AWG 18)	
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers	
Material	ABS (acrylonitrile butadiene-styrene)	
Display type	Without display	
Communication port protocol	2 wires	

Environment

Measurement range	050 °C temperature
Product certifications	CE conforming to EN 61000-6-3[RETURN]RCM[RETURN]EAC[RETURN]ICES-003

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.8 cm	
Package 1 Width	9.7 cm	
Package 1 Length	14.0 cm	
Package 1 Weight	181.82 g	

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins