

# SLPSTXX

SpaceLogic SLA Series Temperature Sensor,  
Color Touchscreen, BACnet MSTP/Modbus  
Outputs, Matte White Housing



## Main

Product or component type	Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control Fan speed controller
Display size	2.4 inch
Location	Living space
Mounting support	Wall-mount
Depth	24 mm
Height	85 mm
Width	115 mm
Network frequency	50 Hz 60 Hz
Standards	UL 916 FCC part 15 class B
Colour	White
Ambient air temperature for operation	0...50 °C
Relative humidity	0...95 %
Sensor type	Transmitter
Surface finish	Matt
Product name	SpaceLogic Room Unit
Function available	With temperature sensor
Range	SpaceLogic

## Complementary

Device presentation	Complete product
Information displayed	Temperature Temperature set point Menu-driven user interface
Connections - terminals	Screw terminal - 2 cable(s) (AWG 24...AWG 18)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers
Control type	tactile
Material	ABS (acrylonitrile butadiene-styrene)
[Us] rated supply voltage	24 V AC 50...60 Hz 20...30 V DC
Display type	Colour touchscreen - 240 x 300 pixels
Communication port protocol	BACnet Modbus
Communication port support	RS485
Measurement accuracy	Typical +/- 0.2 %

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Temperature setting range	10...35 °C 0...50 °C
Measurement range	0...50 °C temperature
Product certifications	CE conforming to EN 61000-6-2 CE conforming to EN 61000-6-3 CE conforming to EN 61326-1 RCM EAC ICES-003 CULus

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	9.67 cm
Package 1 Length	14.0 cm
Package 1 Weight	181.82 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins