



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Product or component type	Battery
Number of rack unit	3U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Additional information	For use with SUA 2200/3000VA 3U models. Can be used with the 5U models with SUA039 extension cable.

Physical

Colour	Black
Height	13.3 cm
Width	48.3 cm
Depth	66 cm
Net weight	63.64 kg
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	No

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28 cm
Package 1 Width	61 cm
Package 1 Length	98 cm
Package 1 Weight	72 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	129 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	574.792 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------