SXWRERCBLE10001

Remote control, SpaceLogic RP Expansion Modules, Bluetooth low energy, connects to the RP-C-EXT-MS-BLE multi-sensor





Main

EcoStruxure Building Operation
SmartX Room Purpose Controller
RP-C-RC-BLE
Schneider Electric
Remote control
3 V DC

Complementary

Range compatibility	EcoStruxure Building Operation software	
Function available	Light control Blind control Temperature adjustment Fan speed control	
Communication port protocol	Bluetooth 5.0 LE	
Display type	FSTN monochrome LCD	
Display resolution	128 x 96 pixels	
Display size	1.4 x 1.7 inch	
Mounting support	Wall Partition wall On fixing base	
Height	143 mm	
Depth	18 mm	
Width	57 mm	

Environment

Standards	EN 60950 EN 62368-1:2014 EN 62311:2008 EN 62479:2010 EN 60730-1 EN 60730-2-11 EN 50491-3
Product certifications	RCM
Electromagnetic compatibility	Electromagnetic emission conforming to EN 61000-6-3 Electromagnetic emission conforming to EN 50491-5-2 Electromagnetic emission class B conforming to FCC part 15 Subpart B Immunity to electromagnetic emissions conforming to EN 50491-5-3 Immunity to electromagnetic emissions conforming to EN 61000-6-2
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	040 °C
Relative humidity	2090 %, non-condensing
IP degree of protection	IP30

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.8 cm
Package 1 Width	6.2 cm
Package 1 Length	14.5 cm
Package 1 Weight	105.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins