

Product data sheet

Characteristics

SZGTP6SB

Left door for 5 fields enclosure, Prisma XS,
IP43, (W) 800 mm x (H) 950 mm



Main

| | |
|------------------------------------|-----------------------------------|
| Range | Prisma |
| Product or component type | Left door |
| Accessory / separate part category | Enclosure accessory Spare part |
| Range compatibility | Prisma Prisma XS |

Complementary

| | |
|-------------------------------|--|
| Enclosure/cubicle description | Wall-mounted enclosure width: 1300 mm depth: 210 mm height: 950 mm |
| Mounting location | Left side for 1300 mm wide enclosure |
| Door opening angle | 110 ° |
| Provided equipment | With locking mechanism |
| Material | Steel |
| Surface finish | Powder coated |
| IP degree of protection | IP43 |
| Net weight | 6.150 kg |
| Width | 748 mm |
| Height | 918 mm |
| Depth | 16 mm |
| Colour tint | White (RAL 9016) |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.0 cm |
| Package 1 Width | 78.0 cm |
| Package 1 Length | 95.0 cm |
| Package 1 Weight | 6.9 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.