## **SZMT2327**

Installation kit for modular device, Prisma XS, continuous DIN rail, (W) 500 mm x (H) 450 mm



| Main                               |                        |
|------------------------------------|------------------------|
| Range                              | Prisma                 |
| Product or component type          | Installation kit       |
| Accessory / separate part category | Installation accessory |
| Range compatibility                | Prisma Prisma XS       |

## Complementary

| Enclosure/cubicle description   | Enclosure depth 210.0 mm                          |
|---------------------------------|---------------------------------------------------|
| Provided equipment              | 1 x cover<br>4 x cover support<br>3 x DIN rail    |
| Type of rail                    | Top hat type TH35-15                              |
| Type of front plate             | Cut-out                                           |
| Number of cut-out               | 3 cut-outs                                        |
| Installed device                | Modular device                                    |
| Number of 18 mm modules per row | 3 x 24                                            |
| 9 mm pitches                    | 144                                               |
| Total number of 18 mm modules   | 72                                                |
| Width                           | 500 mm                                            |
| Height                          | 450 mm                                            |
| Depth                           | 100.0 mm                                          |
| Internal depth                  | 98 mm                                             |
| Net weight                      | 1.500 kg                                          |
| Material                        | Plastic: cover Plastic: cover support Metal: rail |
| Colour                          | White (RAL 9016)                                  |

## Environment

| Ambient air temperature for operation | -540 °C        |
|---------------------------------------|----------------|
| Ambient air temperature for storage   | -540 °C        |
| Standards                             | EN/IEC 61439-1 |

## **Packing Units**

| Unit Type of Package 1       | PCE       |  |
|------------------------------|-----------|--|
| Number of Units in Package 1 | 1         |  |
| Package 1 Height             | 9.000 cm  |  |
| Package 1 Width              | 46.500 cm |  |
| Package 1 Length             | 51.000 cm |  |
| Package 1 Weight             | 2.200 kg  |  |