

# SZMT2426

Installation kit with lowered DIN rail for controlgear, Prisma XS, (W) 500 mm x (H) 600 mm



## Main

Range	Prisma
Product or component type	Installation kit
Accessory / separate part category	Installation accessory
Range compatibility	Prisma Prisma XS

## Complementary

Enclosure/cubicle description	Enclosure depth 210.0 mm
Provided equipment	1 x cover 4 x cover support 4 x DIN rail 8 x DIN rail support
Type of rail	Top hat type TH35-15
Type of front plate	Plain
Installed device	controlgear
Number of 18 mm modules per row	4 x 24
9 mm pitches	192.0
Total number of 18 mm modules	96.0
Width	500 mm
Height	600 mm
Depth	106.0 mm
Internal depth	98 mm
Maximum mounting depth	123 mm
Net weight	2.620 kg
Material	Plastic: cover Plastic: cover support Metal: rail Metal: rail support
Colour	White (RAL 9016)

## Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...40 °C
Standards	EN/IEC 61439-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	61.0 cm
Package 1 Width	51.5 cm
Package 1 Length	9.0 cm
Package 1 Weight	3.62 kg