SZS48

Empty enclosure, Prisma XS, wall-mounted, with door, IP43, (W) 1050 mm x (H) 1250 mm x (D) 210 mm



Main	
Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Empty enclosure
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	1050 mm
Height	1250 mm
Depth	210 mm
Embedding depth	190 mm
Number of 18 mm modules per row	32 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	8 x cable entry plate 1 x double door
Type of front cover	Plain door

Complementary

Cable entry	Entry from the bottom or from the top	
Door type	Internal plain	
Number of locks	3	
Door opening side	Reversible	
Door opening angle	110 °	
Enclosure mounting	Flush Surface Recessed	
Mounting support	Hollow wall Concrete	
9 mm pitches	768.0	
Total number of 18 mm modules	384.0	
[In] rated current	400 A	
Locking options description	Sealable Keylock option	
Enclosure material	Enclosure: powder coated steel Door: powder coated steel Inside enclosure: plastic	
Net weight	31.200 kg	
Colour	White (RAL 9016)	 -

Environment

IP degree of protection	IP43	
IK degree of protection	IK09	
Standards	EN/IEC 61439-1	
	VDE 0660 part 600	

Packing Units

PCE
1
121.0 cm
80.0 cm
147.0 cm
46.5 kg
PAL
3
120.0 cm
80.0 cm
147.0 cm
156.0 kg

Offer Sustainability

EU RoHS Directive	Under investigation	
-------------------	---------------------	--