

# SZS58X

Empty enclosure, Prisma XS, wall-mounted, without door, IP30, (W) 1300 mm x (H) 1250 mm x (D) 210 mm



## Main

Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Empty enclosure
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	1300 mm
Height	1250 mm
Depth	210 mm
Embedding depth	190 mm
Number of 18 mm modules per row	40 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	10 x cable entry plate
Type of front cover	Without

## Complementary

Cable entry	Entry from the bottom or from the top
Enclosure mounting	Flush Surface Recessed
Mounting support	Hollow wall Concrete
9 mm pitches	960
Total number of 18 mm modules	480
[In] rated current	400 A
Enclosure material	Enclosure: powder coated steel Inside enclosure: plastic
Net weight	23.200 kg
Colour	White (RAL 9016)

## Environment

IP degree of protection	IP30
IK degree of protection	IK09
Standards	EN/IEC 61439-1 VDE 0660 part 600

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	131.0 cm
Package 1 Width	22.0 cm
Package 1 Length	128.0 cm
Package 1 Weight	25.6 kg